


KWA – ZULU NATAL

T: 031 701 2619

E: natal@mccc-sa.co.za

Unit 7, Marlmead, 4 Reed Place,
Maxmead, Pinetown, 3610**MULTI CONSTRUCTION
CHEMICALS**<http://www.mcc-sa.co.za>

MULTI BIT 1701 BITUMEN ALUMINIUM COATING

Description

Multibit 1701 is a one-part Bitumen Aluminum Coating.

Typical Applications

Multibit 1701 has excellent adhesion on most interior and exterior surfaces including wood, asbestos, primed metal, polyester, bitumen membranes, concrete surfaces, and various other substrates.

Advantages

1. Easy to apply.
2. Reflective coating.
3. UV Resistant.

Application

Apply coating to a clean, dry and well prepared surface. Stir well with a paddle before using, to prevent aluminum sediment at bottom of tin. Do not thin product, use product as is. Drying time will vary depending on temperature, humidity and location. Apply using brush or roller.

Cleaning

Clean up spills immediately while the coating is still wet with a suitable solvent/turpentine. All tools and implements should be cleaned up with suitable solvents-brush cleaner/turpentine.

Packaging

Multibit 1701 is available in 5L and 20L.

Storage

Multibit 1701 has a minimum shelf life of 12 months.

Keep in a cool storage place.

Coverage

Approx. 8-10 m² per liter depending on porosity and surface texture.

Physical Properties

Density: +/- 0.9 kg/l

Color: Aluminum Finish

Solids: 26-30%

Dry Time: 2 hours at ambient conditions

Health & Safety

1. Product is flammable.
2. Use correct personal protective equipment. i.e., gloves/mask/safety glasses.
3. Seek medical advice in case of emergency.
4. Ensure adequate ventilation when working in confined areas.

Quality Assurance

Multi Construction Chemicals South Africa (PTY) Ltd production and testing programs comply with all local and international testing standards.