

KWA – ZULU NATAL

T: 031 701 2619

E: natal@mcc-sa.co.za

Unit 7, Marlmead, 4 Reed Place,  
Maxmead, Pinetown, 3610

## MULTIFLOW BLOCK PLASTICISER-ACCELERATOR

### Description

Multiflow Block Accelerator is a chloride containing, triple action admixture, which accelerates, plasticizes and entrains air in dry concrete mixes. It increases strength at 24 hours by up to 30%.

Multiflow Block Accelerator enhances the flow properties of dry cement mixes dramatically, resulting in a significant reduction in vibration and cycle times.

Multiflow Block Accelerator furthermore permits the optimisation of the cement content by improving the dispersion of the cement particles with resultant improvement in the final strength and durability.

### Characteristics

Appearance	: Light brown liquid
Density	: 1.075
Colour	: Light Brown
pH	: 5 – 8
Freezing Point	: -15°C
Chloride Content	: +/- 12 %

### Packaging

Multiflow Block Accelerator is supplied in 25 litre and 200 litre drums.

### DIRECTIONS FOR USE

#### Areas of Use:

Cement brick and blocks

### Use and dosage:

Standard dosage: 1.0 kg per 100 kg cement is typical. Site trials are recommended.

Multiflow Block Accelerator can be dosed directly into the gauging water.

The use of Multiflow Block Accelerator is subject to the use of DTU21-4 regulations pertaining to the use of chloride –containing admixtures.

### Important:

If the product freezes, it will regain all its properties once thawed and mixed thoroughly.

Do not use coloured cement without consulting Multi Construction Chemicals.

Multiflow Block Accelerator is classed as an irritant. The use of protective equipment for the skin and eyes is therefore recommended.

In case of spillage mop up with fresh water.